



PREPARED FOR:

RIDL, LTD.
1250 N. SANTA BARBARA
MINDEN, NEVADA 89423

PREPARED BY:

GEOCON CONSULTANTS, INC.
1167 ANNIE COURT, SUITE B
MINDEN, NEVADA 89423



GEOCON

GEOCON PROJECT NO. R8259-06-02

FEBRUARY 2006



Project No. R8259-06-02

February 10, 2006

RIDL, Ltd.
Mr. Andy Hettrick
1250 N. Santa Barbara
Minden, NV. 89423

Subject: DESTINATION NEVADA
CARSON CITY, NEVADA
PRELIMINARY GEOTECHNICAL REVIEW

Dear Mr. Hettrick:

In accordance with your authorization of our proposal; we are submitting the results of our preliminary geotechnical engineering review for the subject site. The accompanying report presents the findings and conclusions from our study.

We identified three adverse conditions on the site that will impact the planned development. The first is the presence of the old Ormsby County Landfill on approximately 13 acres of the site. The volume of landfill material is estimated at 200,000 cubic yards. Complete removal, partial removal or encapsulation of the landfill material are possible mitigations that will be required to develop the affected area. If the landfill material is left in place, appropriate uses would be open space or parking areas. If these types of use are contemplated, an impermeable engineered landfill cap is recommended. However, if the landfill material is left onsite some inherent liability will remain a risk to the owner. An attorney specializing in environmental law should be consulted to put these risks into perspective and to discuss alternatives.

The second adverse condition is the presence of uncontrolled fill derived from alluvium on approximately one third of the site. Mitigation of the uncontrolled fill by one of the following four alternatives should be considered during site planning activities. The uncontrolled fill should be removed and then replaced as structural fill with appropriate testing and observation as recommended herein. Alternatively, deep foundations could be used that would penetrate into firm native soils for support. A third alternative would be to remove and replace a portion of the uncontrolled fill and to design for settlements that exceed normal parameters. If this alternative is chosen, a risk based analysis should be performed. A fourth mitigation alternative would be to revise site plans so as to place parking, lightly loaded structures or open spaces in the areas of most concern.


The third adverse condition identified is the presence of large cut and uncontrolled fill slopes with existing slopes on the order of 1:1 (Horizontal to Vertical) or steeper. These slopes are not considered to be unstable under static conditions but are susceptible to slumping and rock fall especially during seismic shaking. Re-grading of the slopes (2:1) or mechanical stabilization with retaining walls or with rip-rap is likely to be required when site specific geotechnical investigations are conducted. Left in their current configurations, building setbacks from slope crests and toes should be required at a minimum.

The remainder of the site appears to be generally suitable for the proposed development utilizing conventional spread footings or drilled shaft foundations for the larger multistory structures.

Please contact me should you have any questions regarding this report, or if we may be of further service.

Sincerely,

GEOCON CONSULTANTS, INC.



Gary Luce, PE
Senior Project Engineer

GL:jk

(5) Addressee

TABLE OF CONTENTS

1.0 PURPOSE AND SCOPE.....	1
2.0 SITE AND PROJECT DESCRIPTION.....	3
3.0 SOIL AND GROUNDWATER CONDITIONS	4
3.1 Geology and Soil Conditions.....	4
3.2 Groundwater.....	5
4.0 GEOLOGIC HAZARDS	6
4.1 Faulting.....	6
4.2 Liquefaction.....	6
4.3 Slope Stability and Landslide Hazards.....	6
5.0 CONCLUSIONS AND RECOMMENDATIONS	8
5.1 General	8
5.2 General Soil and Excavation Characteristics.....	9
5.3 Closure.....	10
6.0 LIMITATIONS AND UNIFORMITY OF CONDITIONS.....	10

FIGURES

- 1- Vicinity Map
- 2- Site Plan
- 3- Air Photo 2006
- 4- Air Photo 1972
- 5- Conceptual Development Plan
- 6- Geologic Map

APPENDICES

- A Field Investigation
- B Laboratory Testing Program
- C Soil Conservation Service Data

PRELIMINARY GEOTECHNICAL REVIEW

1.0 PURPOSE AND SCOPE

This report presents the results of our Preliminary Geotechnical Review for the proposed Destination Nevada project. Multiple uses are proposed for the site including: a hotel/ casino, commercial/ office tower, shopping mall, condominium/ retail mixed use, and a cinema complex. The approximate site location and boundaries are depicted on the attached Site Vicinity Map and Site Plan, presented as Figures 1 and 2, respectively.

This review is a condition of escrow for RIDL, Ltd who is the potential buyer of the subject site. The project site is an approximately 135 acre area located in the southwest quarter of Section 1, Township 15 North, Range 20 East in Carson City. The property is bounded by Highway 50 and undeveloped land to the north, undeveloped land to the east and south, and light industrial/commercial business to the west (Figure 1).

The purpose of our site review was to generally characterize the soil and geologic conditions, identify any geologic or adverse soil conditions that might impact the development of the site, provide preliminary conclusions regarding liquefaction potential, site grading, seismic design, and to assess the site for the suitability of conventional foundations. During our site review we reviewed geological and soil reports, fault study maps, aerial photographs and performed limited drilling and trenching. The report is considered a Preliminary Geotechnical Review in that no grading plans were available, structure locations and interior roadway layouts were at a conceptual stage, only limited exploration excavations were performed and laboratory testing consisted predominantly of classification and index tests. We recommend that a more thorough design-level geotechnical investigation be completed for the entire site and for each of the larger structures prior to construction.

Prior to conducting our review, the client indicated that there was a pre-existing municipal landfill on the project site and that a substantial area of the project site had been rough graded. The grading included the placement of a substantial amount of uncontrolled fill. The grading was a large scale cut and fills operation intended to create nearly level pads for future light industrial use. The purpose of our subsurface exploration was to evaluate the limits of both the landfill and uncontrolled fill as well as to generally characterize the native soil conditions on the site. The environmental issues related to the dump site will be addressed under a separate cover. In October of 2005, we had completed a Phase I environmental assessment of the site. In addition, the results of our screening level environmental sampling and testing of the landfill debris has been submitted in a separate report.

To aid in preparing this report, we discussed the project with the client and reviewed the following documents:

Conceptual Site Layout, Art Hanafin Architect., September, 2005

Earthquake Hazards Map-New Empire Quadrangle, Nevada Bureau of Mines and Geology, Bell and Trexler, 1979

Soil Survey of Carson City Area, Nevada, United States Department of Agriculture, Soil Conservation Service and Forest Service, 1979

Geocon performed the following scope of geotechnical services:

- Reviewed conceptual site plans to determine exploratory excavation locations.
- Performed a site reconnaissance and marked the proposed exploratory boring locations in the field with stakes and white flagging for subsequent underground utility location purposes.
- As required by law, notified local utility subscribers via Underground Service Alert (USA) at least 48 hours prior to performing subsurface excavations.
- Observed the excavation of 6 exploratory test borings (BH-1 through BH-6) at the site. The borings were advanced with a truck-mounted CME 55 drill rig equipped with hollow-stem augers to depths of approximately 10 to 22 feet below the ground surface (bgs). The approximate locations of the exploratory test borings are depicted on the Site Plan, Figure 2.
- Observed 72 test pits (trenches) (T-01-T-72) at the site. The exploratory test pits were excavated with a Cat 200 Excavator, Cat 310 backhoe, and a Case 580 backhoe.
- Logged the soil test borings under the direction of a Nevada-licensed Civil Engineer in accordance with the Unified Soil Classification System (USCS).
- Obtained debris and soil samples in the old landfill area under the supervision of a Nevada-licensed Certified Environmental Manager. Submitted samples to an outside environmental testing laboratory for chemical analyses. Results and analysis are presented under separate cover.
- Obtained bulk samples and relatively undisturbed soil samples from the test pits and exploratory borings. Logs of the exploratory test excavations and other details of the field investigation are included in Appendix A. Submitted selected soil samples to geotechnical laboratory for testing. Details of the laboratory testing program including test results are included in Appendix B.

2.0 SITE AND PROJECT DESCRIPTION

The project site is an approximately 135-acre area located approximately 5 miles east of downtown Carson City on the south side of Highway 50 (Figure 3). Current access to the site is from US Highway 50 and Drako Way. The terrain is flat to rolling with elevations ranging from 4,825 feet in the northeast corner of the parcel to 4,720 feet in the flat lying southwest portion. The site is currently vacant except for two warehouse structures (Computer Corp, Inc.) and a single family residence located on the northeast parcels (8-521-23 and 24). The southern half of the site was previously rough graded in the early 1980s for proposed commercial development. An abandoned landfill is located in the west central portion of the site. This landfill is identified as the former Ormsby County Landfill on the previous owners' deed. Several topographic "breaks" are present across the site and represent the edges of cut or fill slopes. The most prominent of these breaks is the northeast-southwest trending fill slope along the southerly portion of the old Landfill. The eastern boundary of the site has two large cut slopes constructed during the previous grading operations. The parcel is generally covered with native vegetation primarily consisting of sagebrush, native grasses and other shrubs. Several stockpiles consisting of soil, rock and landscape debris (vegetation clippings, etc.) were observed on the easterly and central portion of the site.

Examination of historic aerial photography indicates the site was formerly crossed by an incised drainage that traversed from northeast to southwest. In addition, a second incised drainage bounded the southwesterly edge of the property (Figure 4).

Approximately 20 acres of the site is underlain by uncontrolled fill (not including the old landfill). The uncontrolled fill area is generally located on the southerly portion of the site.

There are numerous graded dirt roads on the site of which some are related to previous development plans. Power lines cross the site northeasterly along Astro Drive and northerly along both east and west property lines. There is a gas line located on the northwest part of the property. The adjacent properties to the west have improvements that include commercial / light industrial buildings.

At the time of this report, only a conceptual layout for the Destination Nevada Project was available. Multiple proposed uses for the site including: a hotel/casino, commercial/office tower, shopping mall, condominium/retail mixed use, and a cinema complex all with associated landscaping and parking areas (Figure 5).

Preliminary plans by others indicate the proposed depot for the Virginia and Truckee Railroad reconstruction project may be constructed directly west of the site. Additional planned developments adjacent to the site on the south include two museums proposed to be constructed on BLM land.

3.0 SOIL AND GROUNDWATER CONDITIONS

The soil conditions observed in our exploratory borings and test pits were relatively consistent across the site (except for the landfill area). The following soil descriptions include the Unified Soil Classification System (USCS) symbol where applicable. Please refer to the exploratory excavation logs included in Appendix A for vertical extents of the materials encountered at each exploratory location.

3.1 Geology and Soil Conditions

Geologic mapping of the site is published on the Geologic Map of Lyon, Douglas and Ormsby Counties, Nevada, Nevada Bureau of Mines and Geology, Bulletin 75, 1969. This geologic map shows the site to be located on the western flanks of the Pinenut Mountains. The geology of the site is predominately older (early Pleistocene and Pliocene) alluvial fan deposits, locally referred to as Alluvial-fan deposits of Morgan Mill. South and East of the site are middle Jurassic volcanic and metavolcanic rocks. The alluvial fan sediments are derived from intermediate volcanic rocks with lesser metamorphic rocks, and minor granitic rocks. A mixture of moderately thick deposits (60 to 300 feet) of poorly to moderately sorted fluvial gravel, sand, and silt typically characterizes these sediments. The sediments are typically highly dissected by deep channels, but original low-relief depositional surfaces are preserved locally. The volcanic and metavolcanic rocks found near the site consist of andesite, dacite, breccias and conglomerates. A Geologic Map of the surface of the site (1" to 600') was developed within our scope of work (Figure 6). The map was developed from both field observations and interpretation of the aerial photographs of the site.

The Soil Conservation Service (SCS) generally characterizes soils within the site as the Reno gravelly clay loam. This alluvial material formed from basaltic rock parent material. The surface layer is typically grayish brown gravelly clay loam about 3 inches in thickness. The subsoil is light gray, sandy clay about 17 inches thick. The next layer is a highly cemented hardpan about 9 inches thick. Below this to a depth of 60 inches is light brownish gray, stratified gravelly and very gravelly loamy sand. Permeability of this material is moderately slow. Available water capacity is very low. The Soil Conservation Service Maps and selected SCS data for the project site are presented in Appendix C for use as a reference to the following discussion.

Native soils encountered on the site generally consist of medium dense to dense, moist to dry, Silty Sand (SM) to Sandy Gravel (GM) with small amounts of Silt (ML), Clayey Sand (SC) and Lean Clay (CL). Native soils were only encountered in an undisturbed state in limited areas, particularly north of Astro Way and along cut slopes on the east side of the site.

The soils underlying the site including the uncontrolled fill were generally consistent with the map descriptions of the alluvial fan deposits. Soils encountered over and within the debris associated with the old landfill were also consistent with alluvial fan deposits. The uncontrolled fill was up estimated to be as deep as 110 feet near the southwest boundary of the site. In order to evaluate the character of the uncontrolled fill, exploration was conducted both at the crest and toe of the large fill slopes. The fill material was found to be relatively consistent alluvial materials from top to bottom. Attempts to drill through the fill failed due to refusal at shallow depths on cobble materials. The uncontrolled fill generally decreased in thickness to the northeast. The current owner reported to us that some organic debris was deposited in the extreme edge of the uncontrolled fill along the south and west boundaries of the property. The risk of settlement during dynamic shaking or under construction loads in the areas of uncontrolled fill (including the landfill) is considered to be moderate to high.

The landfill area is located near the center of the site just south of Astro Way. Our exploration indicated that the debris increases in thickness from north to south ranging from less than a foot to as much as 22 feet. Typical soil cover over the debris ranged from less than one foot to six feet below the existing surface. The average thickness of debris was approximately 8 feet based on all of our test pits in the landfill area. The debris encountered was consistent with household refuse and general construction debris. Debris types included glass, wire, fabricated metal, wood, plastic, concrete, asphalt and other similar materials all within a silty sand soil matrix with ash which is consistent with a "burn dump". It is noted that refusal on concrete was encountered at a few test pit locations and the lone borehole attempted in the landfill area. Therefore the volume estimate (200,000 cy) should be viewed as a minimum.

3.2 Groundwater

Groundwater was not encountered in any of the exploratory excavations during the field investigation conducted in October and November, 2005. It is inferred that the depth to groundwater is greater than 100 feet below the existing ground surface on the majority of the site where construction is planned. The site ranges from about 4,640 to 4,760 feet above mean sea level. The permanent groundwater table should be at an elevation near the level of the Carson River (approximate elevation 4,590) located approximately one-quarter mile south of the site. It is possible that seasonal perched groundwater may occur at higher elevations in some areas of the site.

4.0 GEOLOGIC HAZARDS

4.1 Faulting

Carson City is located near active faults which are considered capable of producing significant ground motions due to seismic events. Based on the results of the site investigation and review of geologic maps and reports, the site is not located on any known active or potentially active fault traces.

The nearest potentially active faults are located approximately one and one-half mile west of the site near the intersection of US 50 with Edmonds Drive. These faults are relatively small and not considered to govern design at the site. Ground shaking intensities for design considerations should be governed by seismic events occurring on the larger regional faults at the base of the Carson Range located approximately four miles west of the site (i.e. the Carson City Fault). Faulting along the Carson Range has been evaluated by the Nevada Bureau of Mines and Geology to be capable of producing earthquake Richter Magnitudes on the order of 7.4 with peak ground accelerations as high as 0.7g. These values are equivalent to Modified Mercalli Intensities of X or greater.

The seismic risk at the site is not considered significantly greater than that of the surrounding developments and the Carson City area in general. Seismic design of the structures should be performed in accordance with the latest version of the International Building Code (IBC).

4.2 Liquefaction

Liquefaction of granular soils can be caused by strong vibratory motion due to earthquakes. Soils that are highly susceptible to liquefaction are loose, granular and saturated. The liquefaction of soils causes surface distress, loss of bearing capacity, and settlement of structures that are founded on the soils. Based on review of soil types, relatively high in place soil density, depth to groundwater, and the seismic accelerations anticipated at the site, it is our opinion that the potential for seismic related ground movement resulting from liquefaction is very low.

4.3 Slope Stability and Landslide Hazards

No significant landslide hazards or slope stability issues are known to exist on the site except as noted below. Relatively large cut and fill slopes are present along the southeasterly and south property boundaries. These slopes are constructed at slopes of approximately 1:1 (Horizontal to Vertical). Additional smaller slopes throughout the site are in similar configurations. The recommended unstabilized slope angle for the native soils encountered on the site would be 2:1. While the steeper slopes are not believed to be prone to landsliding, they are believed to be capable to raveling (rock fall) and slumping especially if subjected to seismic shaking. These slopes should be regarded to 2:1 or be mechanically stabilized using large rip-rap or retaining walls. If left in their current configurations,

building setbacks from both toes and crests should be developed during site specific design level geotechnical investigations. The interior slopes are likely to be removed or modified during site development and may be mitigated during this process.

5.0 CONCLUSIONS AND RECOMMENDATIONS

5.1 General

Based upon the results of our geotechnical review the site is generally suitable for the proposed development provided that the identified adverse conditions are mitigated properly. The conclusions and recommendations presented in this report are provided for forward planning, and should be considered preliminary. Grading and utility installations should proceed with only ordinary effort for sandy to gravelly soils. No other geologic hazards related to high ground water, expansive or collapsible soils, landslides or faulting are believed to exist on the site.

Environmental risks and mitigations are not specifically addressed herein. A separate report by Geocon to the client addressing environmental issues related to the old landfill on the site should be reviewed in conjunction with consultation with legal counsel.

Specific geotechnical mitigation measures will need to be developed by site specific investigations when final site layouts, grading plans and structural details are available. A brief summary of our findings is listed below:

- Our field investigation indicates that the undisturbed portions of the site are primarily underlain by alluvial fan deposits comprised interbedded layers of sandy gravels, silty to clayey sand and poorly graded sand with scattered thin clay lenses.
- Uncontrolled alluvial fill covers approximately 20 acres of the site. Construction in these areas will require some form of mitigation or removal. Site specific design level geotechnical investigations will be required.
- Approximately 13 acres of the site is underlain by up to 22 feet of debris laden landfill materials with an estimated volume of 200,000 cubic yards. The landfill materials will need to be removed or mitigated in some fashion prior to construction over them. Alternatively, the site could be planned around the landfill with appropriate construction or open space placed in the landfill area. These issues need to be addressed in consultation with environmental counsel and the permitting issues explored with the appropriate governing agencies including Carson City and NDEP.
- Groundwater was not encountered during our exploration and is believed to be well below any potential construction depths. It is possible that perched groundwater could be may occur at potential construction depths on a seasonal basis. Exploration of the site should further address this issue and pot holing of the site would be recommended prior to bidding grading and again at the time equipment is mobilized to the site.
- There are no known surface expressions of active faults underlying the site. Potential seismic hazards at the site will likely be associated with possible moderate to strong ground shaking

from an event along regional active faults. Structures should be designed in accordance with the most current version of the IBC as adopted by Carson City.

- Soil corrosion potential data and our local experience indicates that soils are not aggressive for either Type II or Type IP concrete.
- The proposed structures should be able to be supported on conventional shallow foundations in native undisturbed soils or where the uncontrolled fill has been removed and replaced or on deep foundations as determined by site specific design level geotechnical investigations.

5.2 General Soil and Excavation Characteristics

Prior to the commencement of mass grading, the structures that are to be removed should be demolished. Demolition should be monitored by Geocon to confirm the complete removal of foundation elements. Utilities should be removed or abandoned in place as appropriate to the planned construction and as permitted by the specific regulatory agency. If the debris in the landfill area is to be removed from the site, the process should be completed prior to the commencement of general grading.

Clearing and grubbing should require minimal depths over most of the site. In areas of the site where native sagebrush and other vegetation is present, clearing and grubbing will typically require from 2 to 4 inches of removal. Removed materials should be disposed of off site or placed in landscape areas only.

In our opinion, grading and excavations within the alluvial materials (excluding the landfill area) may be accomplished with light to moderate effort with conventional heavy-duty grading/excavation equipment. Excavations are not anticipated to generate significant quantities oversized material (greater than six inches in dimension) that would require special handling or exporting from the site. Some of the native materials will probably require "proof rolling" (NDOT Specifications) rather than conventional nuclear densometer testing due to the amount of gravel.

Excavated soils generated from cut operations at the site including native undisturbed and uncontrolled fill materials are generally suitable for use as engineered fill in structural areas after removal of oversize materials or any organic debris

Fills placed on slopes greater than 10% will require "keying" into the native materials. This will be necessary if the uncontrolled fill is removed and replaced.

Temporary excavations, such as utility trench sidewalls excavated within undisturbed alluvium should remain near-vertical to depths of at least five feet. Some minor sloughing should be expected within some of the cleaner sand lenses. Excavation support per OSHA Standards will need to be strictly enforced.


5.3 LIMITATIONS AND UNIFORMITY OF CONDITIONS

The preliminary recommendations of this report pertain only to the site investigated and are based upon the assumption that the soil conditions do not deviate from those disclosed in the investigation. This review is written with the explicit understanding that site specific design level geotechnical investigations will be conducted prior to the construction of any of the planned structures.

This report is issued with the understanding that it is the responsibility of the owner or their representative to ensure that the information and recommendations contained herein are brought to the attention of the design team for the project and incorporated into future project plans.

The findings of this report are valid as of the present date. However, changes in the conditions of a property can occur with the passage of time, whether they be due to natural processes or the works of man on this or adjacent properties. In addition, changes in applicable or appropriate standards may occur, whether they result from legislation or the broadening of knowledge. Accordingly, the findings of this report may be invalidated wholly or partially by changes outside our control. Therefore, this report is subject to review and should not be relied upon after a period of two years.

Our professional services were performed, our findings obtained, and our recommendations prepared in accordance with generally accepted geotechnical engineering principles and practices used in Carson City, Nevada in February 2006. No warranty is either expressed or implied.



SITE VICINITY MAP

GEOCON

CONSULTANTS, INC.

1167 ANNIE COURT - SUITE B - MINDEN, NV 89423

PHONE 775 267-0566 -- FAX 775 267-0728



Destination Nevada

Carson City,
Nevada

R8259-06-02

Feb-06

Figure 1



Air Photo-2006

Destination Nevada

Carson City,
Nevada

GEOCON

CONSULTANTS, INC.

1167 ANNIE COURT - SUITE B - MINDEN, NV 89423

PHONE 775 267-0566 -- FAX 775 267-0728



R8259-06-02

Feb-06

Figure 3



Jun-72

1:15,000

Air Photo-1972

GEOCON

CONSULTANTS, INC.

1167 ANNIE COURT - SUITE B - MINDEN, NV 89423

PHONE 775 267-0566 -- FAX 775 267-0728




Destination Nevada

Carson City,
Nevada

R8259-06-02

Feb-06

Figure 4



RETAIL MIXED USE	1,628,713 SQ.FT.	HOTELS	1,025,235 SQ.FT.
CASINO	1,016,000 SQ.FT.	MUSEUM (PUBLIC USE)	482,152 SQ.FT.
RAILROAD STATION & FACILITIES	160,000 SQ.FT.	CONDOMINIUMS	2,652,408 SQ.FT.
COMMERCIAL OFFICE/ MIXED USE BLDGS.	2,070,180 SQ.FT.	PUBLIC FACILITY	364,893 SQ.FT.
CINEMA & IMAX	85,283 SQ.FT.	PUBLIC PARKING STRUCTURE	359,861 SQ.FT.


EST. TOTAL SQUARE FOOTAGE: 9,844,725 SQ.FT.

EST. PUBLIC PARKING 10,500 SPACES

FIGURE 5

PROJECT
DESTINATION NEVADA
ST. CARSON CITY
OVERALL SITE PLAN

HANNAFIN DESIGN
ASSOCIATES
Design Development Planning
111 N. CARSON STREET, SUITE 200, CARSON CITY, NV 89701
PHONE: (775) 882-6455 FAX: 882-1444
E-MAIL: info@hannafinarchitects.com



LEGEND

Uc	Uncontrolled Fill	Qcol	Silty Sand with Cobbles, Gravel and Boulders
Lf	Landfill Area	Qcol/Tv	Silty Sand with Cobbles, Gravel and Boulders over Shallow Andesitic Bedrock
Qal	Sand, Silt, gravel		

Geologic Map

GEOCON
CONSULTANTS, INC.

1167 ANNIE COURT - SUITE B - MINDEN, NV 89423
PHONE 775 267-0566 - FAX 775 267-0728



Destination Nevada

Carson City,
Nevada

R8259-06-02

Feb-06

Figure 6

APPENDIX

A

APPENDIX A

FIELD INVESTIGATION

The field investigation was performed in October and November of 2005. The field investigation consisted of the excavation of six exploratory borings (BH-1 through BH-6) and seventy-three exploration test pits (T-1 through T-73) at the approximate locations shown on the Site Plan, Figure 2.

The borings were excavated using a truck-mounted CME 55 drill rig equipped with 8-inch outside diameter (OD) hollow-stem augers. Sampling was accomplished using a 140-pound hammer with a 30-inch drop. Samples were obtained with both a "Standard Penetration Sampler" (1.4 inch ID) and a 2.5-inch OD, split spoon California sampler. The number of blows required to drive the sampler the last 12 inches of the 18-inch sampling interval were recorded on the boring logs. Upon completion, the borings were backfilled with native cuttings in accordance with State of Nevada standards.

The exploratory test pits were excavated by the use of trackhoes and rubber tired backhoes. The specific equipment is noted on the exploratory logs. Approximately fifty of the test trenches were intended to define the limits of the old "Ormsby County Landfill" and to allow for both geotechnical and environmental sampling. Samples for both environmental and geotechnical purposes were recovered by bulk sampling techniques. Geotechnical test data is included in Appendix B. Environmental test data has been transmitted to the client under separate cover.

The soil conditions encountered in the borings and test pits were visually examined, classified, and logged in general accordance with the American Society for Testing and Materials (ASTM) Practice for Description and Identification of Soils (Visual – Manual Procedure D2488-90). The logs of the exploratory excavations are presented herein.

COMMENTS:

LOG OF BORING No. BH-1

LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 3.0

WATER DEPTH:

LOG OF BORING DESTINATION NEVADA GPJ GEOCON NV. GDT 2/8/06



GEOCON
CONSULTANTES 3D

PROJECT:

Destination Nevada Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-1

COMMENTS:

LOG OF BORING No. BH-2


LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 16.0

WATER DEPTH:

GEOCON
CONSULTANTS INC

PROJECT:

Destination Nevada
Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-2

COMMENTS:

LOG OF BORING No. BH-3

LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 7.8

WATER DEPTH:

MISC. TESTS	R VALUE	DESCRIPTION / CLASSIFICATION						LAYER ELEV./DEPTH
		UNIT DRY WEIGHT, PCF	WATER CONTENT, %	LIQUID LIMIT, %	PLASTICITY INDEX, %	PASSING NO. 200 SIEVE, %	DEPTH, FT	
								SURFACE ELEVATION: 4720.0
								SILT: stiff, moist, gy, w/ gravel, COLLUVIUM/EOLIAN
								Silty SAND: dense, moist, yel brn, w/ gravel, ALLUVIUM
							5	Sandy SILT: stiff, moist, gy, w/ black spots, w/ gravel, ALLUVIUM
								Silty SAND: v dense, moist, orange- yel brn, / gravel, oxid, ALLUVIUM



GEOCON
CONSULTANTS (P)

PROJECT:

Destination Nevada Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-3

COMMENTS:

LOG OF BORING No. BH-4

LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 5.8

WATER DEPTH:

MISC. TESTS	R VALUE	UNIT DRY WEIGHT, PCF	WATER CONTENT, %	LIQUID LIMIT, %	PLASTICITY INDEX, %	PASSING NO. 200 SIEVE, %	DEPTH, FT	DESCRIPTION / CLASSIFICATION		LAYER ELEV./ DEPTH
								SYMBOL	SAMPLE	
										SURFACE ELEVATION: 4760.0
										Silty SAND: loose -dense, dry - moist, red brn, w/ grav and cob, COLLUVIUM
										4756.5
										3.5
										Silty GRAVEL: v dense, dry - sli moist, lt red brn, w/ sand, refusal at 5.8 ft, COLLUVIUM
										4754.2
										5.8



PROJECT:

Destination Nevada
Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-4

COMMENTS:

LOG OF BORING No. BH-5

LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 1.6

WATER DEPTH:

PROJECT:

Destination Nevada Carson City

Figure-5



GEOCON
CONSULTANTS, INC.

JOB NO.: R8259-06-01

DATE: 11/7/05

COMMENTS:

LOG OF BORING No. BH-6

LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 5.9

WATER DEPTH:



GEOCON
CONSULTANTS LTD.

PROJECT:

Destination Nevada Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-6

COMMENTS:

LOG OF BORING No. BH-7


LOGGED BY: J. HARRIS

DATE: 11/3/05

EQUIPMENT: CME 55

TOTAL DEPTH: 10.9

WATER DEPTH:



LOG OF BORING DESTINATION NEVADA GPJ GEOCON NV GDT 2/8/06

GEOCON
CONSULTANTS, INC.

PROJECT:

Destination Nevada
Carson City

JOB NO.: R8259-06-01

DATE: 11/7/05

Figure-7

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T1		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
					ELEV. (MSL.)	DATE COMPLETED						
0					MATERIAL DESCRIPTION							
0	o o o	GW			ALLUVIUM Very dense to cemented, slightly moist, brown, well-graded Silty SAND and sub-angular gravel							
2	o o				TRENCH TERMINATED AT 3 FEET							

Figure 1, Log of Trench T1, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T2		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		ML		ML	ALLUVIUM Loose to firm, dry to damp, brown, fine Sandy SILT with some sub-angular gravel				
2					Very firm to hard, damp, brown, very fine Sandy SILT, with some clay and pebble-sized rock				
TRENCH TERMINATED AT 3.5 FEET									

Figure 2, Log of Trench T2, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF
SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T3	ELEV. (MSL.)	DATE COMPLETED	10/18/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0					MATERIAL DESCRIPTION						
				ML	ALLUVIUM Loose to firm, dry to damp, fine Sandy SILT						
2				ML	Hard, damp, brown, fine Sandy SILT, with trace clay and pebble-sized rock						
				SW/GW	Very dense, damp, moist, Clayey fine to medium SAND, with pebble-sized rock						
TRENCH TERMINATED AT 3.5 FEET											

Figure 3, Log of Trench T3, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T4	ELEV. (MSL.)	DATE COMPLETED	10/18/2005	PENETRATION RESISTANCE (BLOWS/FT)	DRY DENSITY (PCF.)	MOISTURE CONTENT (%)
0				SM GW	MATERIAL DESCRIPTION						
ALLUVIUM											
0		° ° ° ° °			Loose to firm, dry to damp, Silty fine SAND, with clay and some gravel						
2					Hard, damp, light brown, Clayey fine SAND and GRAVEL						
TRENCH TERMINATED AT 3.5 FEET											

Figure 4, Log of Trench T4, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T5	ELEV. (MSL.)	DATE COMPLETED	10/18/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0					MATERIAL DESCRIPTION						
0				SM	ALLUVIUM						
0				CL	Loose, dry, brown, Silty fine SAND						
0					Hard, damp to slightly moist, brown, fine Sandy CLAY, with minor caliche						
2				GW	Very dense, damp, brown, Clayey fine to medium SAND, with gravel						
					TRENCH TERMINATED AT 3.5 FEET						

Figure 5, Log of Trench T5, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T6	ELEV. (MSL.)	DATE COMPLETED	10/18/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0				SM GC	ALLUVIUM						
MATERIAL DESCRIPTION											
0				SM GC	ALLUVIUM	Loose, dry, brown, Silty fine SAND Stiff to hard, damp, brown, Sandy CLAY and GRAVEL					
2				GW		Dense, damp, brown, Clayey fine SAND and GRAVEL, caliche lenses					
TRENCH TERMINATED AT 3 FEET											

Figure 6, Log of Trench T6, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T7		PENETRATION RESISTANCE (BLOWSWIFT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM CL	ALLUVIUM Loose, dry, brown, Silty fine SAND Firm to stiff, damp, brown, fine Sandy CLAY, with gravel and caliche lenses				
2				SM	Dense, damp, brown, Silty fine SAND, with caliche stringers and gravel				
4					TRENCH TERMINATED AT 4.5 FEET				

Figure 7, Log of Trench T7, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T8	ELEV. (MSL.)	DATE COMPLETED	10/18/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0					MATERIAL DESCRIPTION						
0				ML	FILL Loose, dry, light tan, Silty fine SAND, with some gravel						
2				SM	ALLUVIUM Medium dense, dry, brown, Silty very fine SAND						
2				CL	Stiff to hard, slightly moist, brown, fine Sandy CLAY, with clayish stringers						
4					TRENCH TERMINATED AT 4.5 FEET						

Figure 8, Log of Trench T8, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T9		PENETRATION RESISTANCE (BLOW/SFT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0					MATERIAL DESCRIPTION				
0				ML	FILL Loose, dry, light tan, Silty fine SAND, with some gravel				
2				SM/SC	ALLUVIUM Very dense, slightly moist, brown, Silty to Clayey fine SAND - gravel to small boulder-sized rock				
4					TRENCH TERMINATED AT 5.5 FEET				

Figure 9, Log of Trench T9, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS ... SAMPLING UNSUCCESSFUL ... STANDARD PENETRATION TEST ... DRIVE SAMPLE (UNDISTURBED)
 ... DISTURBED OR BAG SAMPLE ... CHUNK SAMPLE ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T10		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		SM CL			ALLUVIUM Loose, dry, light tan, Silty fine SAND, with gravel Firm to stiff, slightly moist, brown, fine Sandy CLAY, with caliche stringers				
2									
4					TRENCH TERMINATED AT 5.5 FEET				

Figure 10, Log of Trench T10, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF
SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T11		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		SC/GW			FILL Loose to firm, SAND, CLAY and GRAVEL mixture				
2		CL			ALLUVIUM Firm to medium dense, moist, brown, fine Sandy CLAY				
3		CL			Hard, slightly moist, light brown, fine Sandy CLAY, with caliche				
4					TRENCH TERMINATED AT 4.5 FEET				

Figure 11, Log of Trench T11, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 12, Log of Trench T12, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/06/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.


DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T13	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.) _____ DATE COMPLETED <u>10/18/2005</u> EQUIPMENT <u>JD 310G BACKHOE</u>			
MATERIAL DESCRIPTION								
0					COVER FILL LANDFILL DEBRIS Loose, dark brown, fine Sandy SILT with glass and metal debris			
4	T13-3 1625 PID = 0 T13-4 1630d PID = 0			ML	ALLUVIUM Firm, moist, brown, Sandy CLAY, with gravel			
TRENCH TERMINATED AT 5 FEET								

Figure 13, Log of Trench T13, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	 ... DISTURBED OR BAG SAMPLE	 ... CHUNK SAMPLE	 ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 14, Log of Trench T14, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 15, Log of Trench T15, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T16		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				ML	LANDFILL DEBRIS Abundant concrete rubble and one tire near surface Loose, dry to damp, dark brown, fine Sandy SILT with abundant glass fragments, bottles, metal brick, and wood debris				
T16-2 0840 PID = 0									
2									
4									
6									
T16-7 0850 PID = 0				GW	ALLUVIUM Firm to hard, damp, brown, fine Sandy SILT and CLAY, with gravel and claiche stringers				
8									
10									
					TRENCH TERMINATED AT 11 FEET				

Figure 16, Log of Trench T16, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF
SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 17, Log of Trench T17, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE		<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE	

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T18		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)							
					ELEV. (MSL.)	DATE COMPLETED										
MATERIAL DESCRIPTION																
COVER FILL																
0				ML	LANDFILL DEBRIS											
2					Loose, dry to damp, dark brown, fine Sandy SILT and Silty fine SAND, with abundant glass fragments, bottles, metal, brick											
4																
6	T18-COMP 0945 PID = 0															
8																
10																
12				ML	ALLUVIUM Hard, damp, tan, fine Sandy SILT											
14	T18-14 0950															
	PID = 0				TRENCH TERMINATED AT 14.5 FEET											

Figure 18, Log of Trench T18, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T19	ELEV. (MSL.)	DATE COMPLETED	10/19/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0	T19-0-3 1010 PID = 0				MATERIAL DESCRIPTION						
LANDFILL DEBRIS - with abundant brick and glass fragments											
2											
4	° ° ° ° °	GW			ALLUVIUM Firm to hard, damp, brown, fine Sandy CLAY and GRAVEL, clayey sand						
6					TRENCH TERMINATED AT 6 FEET						

Figure 19, Log of Trench T19, page 1 of 1

TRENCH LOG DESTINATION TRENCHES GPJ 02/01/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T20	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.) _____ DATE COMPLETED <u>10/19/2005</u> EQUIPMENT <u>JD 310G BACKHOE</u>			
MATERIAL DESCRIPTION								
0				SM/CL	ALLUVIUM Loose, dry, dark brown, Silty SAND and firm, moist, Sandy CLAY			
2			GW		Dense to hard, damp, brown, Clayey SAND/Sandy CLAY with gravel			
4					TRENCH TERMINATED AT 4 FEET			
6								
8								
10								

Figure 20, Log of Trench T20, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 21, Log of Trench T21, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T22		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0					MATERIAL DESCRIPTION				
2	T22-2 1250 PID = 0			SM	FILL Loose, dry, brown, Silty SAND with gravel 10 ml visqueen				
4				SM/ML	ALLUVIUM Medium dense to dense, dry, Silty SAND/Sandy SILT				
					TRENCH TERMINATED AT 5.5 FEET				

Figure 22, Log of Trench T22, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T23	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.) _____ DATE COMPLETED <u>10/19/2005</u> EQUIPMENT <u>JD 310G BACKHOE</u>			
MATERIAL DESCRIPTION								
COVER FILL								
0				SM	LANDFILL DEBRIS - glass, metal, concrete debris, tire, wire, cable Loose, dry to damp, dark brown, Silty fine SAND			
1								
2								
4								
6								
8								
10								
12								
14								
16								
					TRENCH TERMINATED AT 17 FEET			

Figure 23, Log of Trench T23, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T24		PENETRATION RESISTANCE (BLOWS/FT)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0					MATERIAL DESCRIPTION				
		COVER FILL							
2		SM			LANDFILL DEBRIS - ash, brick, glass, and metal debris				
4					Loose, dry to damp, dark brown, Silty fine SAND				
6									
8									
10									
12		ML			ALLUVIUM Slightly cemented, damp, brown, fine Sandy SILT				
					TRENCH TERMINATED AT 13 FEET				

Figure 24, Log of Trench T24, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T25		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0					COVER FILL				
2									
4				SM	LANDFILL DEBRIS				
6					Loose, damp to moist, dark brown, Silty fine SAND, with ash, concrete blocks, timber, glass, metals, pipe, tires, plastic wrapping				
8									
10									
12									
14									
16									
18	T25-18 1430				TRENCH TERMINATED AT 18 FEET				
	PID = 4.0								

Figure 25, Log of Trench T25, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/01/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 26, Log of Trench T26, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/06/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T27		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	COVER FILL				
					Loose, dry, light gray, Silty fine SAND				
10					TRENCH TERMINATED AT 10 FEET TRENCH COLLAPSED				

Figure 27, Log of Trench T27, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T28		PENETRATION RESISTANCE (BLOWSIFT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
					EQUIPMENT	JD 310G BACKHOE			
0				SM	MATERIAL DESCRIPTION				
2					COVER FILL				
4					Loose, dry, light gray, Silty fine SAND				
6									
8									
10					TRENCH TERMINATED AT 10 FEET TRENCH COLLAPSED				

Figure 28, Log of Trench T28, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 01/31/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 29, Log of Trench T29, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T30	ELEV. (MSL.)	DATE COMPLETED	10/19/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0				SM	COVER FILL						
2					Loose, dry, dark yellowish brown, Silty SAND LANDFILL DEBRIS - tires, glass wood ash, fabricated metal, wire, plastic						
					TRENCH TERMINATED AT 2.5 FEET						

Figure 30, Log of Trench T30, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T31		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM SC/CL	ALLUVIUM Loose, dry, dark yellowish brown, Silty SAND with gravel and cobbles				
2					Dense, slightly moist, dark brown to yellowish brown, Sandy Gravelly CLAY/Clayey SAND				
					TRENCH TERMINATED AT 2.5 FEET				

Figure 31, Log of Trench T31, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T32	ELEV. (MSL.)	DATE COMPLETED	10/19/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
MATERIAL DESCRIPTION											
0					LANDFILL DEBRIS - Concrete slab 10-12" thick, CMU, red brick, rebar, trace glass, wire						
2											
4				GM	ALLUVIUM Dense, slightly moist, dark yellowish brown, Silty Sandy GRAVEL with cobbles						
					TRENCH TERMINATED AT 5 FEET						

Figure 32, Log of Trench T32, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	 ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	 ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.




Figure 33, Log of Trench T34, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE		<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE	

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T33		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0					LANDFILL DEBRIS				
2									
4		SC		SC	ALLUVIUM				
TRENCH TERMINATED AT 4 FEET									

Figure 34, Log of Trench T33, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T35		PENETRATION RESISTANCE (BLOWSFIT)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	COVER FILL Loose, dry, dark yellowish brown, Silty SAND				
2					LANDFILL DEBRIS Debris laden fill: Sheet metal, Chain, wire, trace glass and plastic				
4									
6				CL	ALLUVIUM Stiff, moist, yellowish brown, Sandy CLAY				
				SM	Medium dense, dry, dark yellowish brown, Silty SAND				
TRENCH TERMINATED AT 7 FEET									

Figure 35, Log of Trench T35, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03




Figure 36, Log of Trench T36, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE		<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE	

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T37		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				CL	ALLUVIUM				
1				GM	Stiff, dry, dark brown, Sandy CLAY				
2					Dense, dry, dark yellowish brown, Sandy GRAVEL with claiche and cobbles				
					TRENCH TERMINATED AT 2.5 FEET				

Figure 37, Log of Trench T37, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T38		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		CL SM			ALLUVIUM Hard, dry, dark brown, Silty CLAY with gravel Very dense, dry, yellowish brown, caliche cemented, Silty SAND	REFUSAL - TRENCH TERMINATED AT 1.5 FEET			

Figure 38, Log of Trench T38, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T39		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	COVER FILL Loose, dry, dark yellowish brown, Silty SAND				
2									
4					LANDFILL DEBRIS - glass, lots of ash				
					TRENCH TERMINATED AT 5 FEET				

Figure 41, Log of Trench T39, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS		<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
		<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T40	ELEV. (MSL.)	DATE COMPLETED	10/19/2005	PENETRATION RESISTANCE (BLOWSIFT)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0				ML	MATERIAL DESCRIPTION						
				CL/ML	ALLUVIUM	Loose, dry, yellowish brown, fine Sandy SILT					
2					Dense, dry, Silty CLAY to cemented SILT						
					TRENCH TERMINATED AT 3.75 FEET						

Figure 42, Log of Trench T40, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T41		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	COVER FILL Loose, dry, dark yellowish brown, Silty SAND				
2									
4				SM	LANDFILL DEBRIS - Silty SAND with 1-3' concrete slab, 4-6" thick				
6									
8					TRENCH TERMINATED AT 8 FEET				

Figure 43, Log of Trench T41, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T42		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		SM/GM		ALLUVIUM Loose to medium dense, dry, dark yellowish brown, Silty SAND with sandy gravel 12-inch cobbles					
2									
4									
6					TRENCH TERMINATED AT 6 FEET				

Figure 44, Log of Trench T42, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T43		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				GM	COVER FILL Sandy GRAVEL				
2				SM	Loose, dry, dark brown, Silty SAND				
4				GM	LANDFILL DEBRIS Medium dense, moist, dark brown, Silty Sandy GRAVEL, trace debris asphalt and concrete				
6				SC	ALLUVIUM Dense, dry, brown, Clayey SAND with gravel				
TRENCH TERMINATED AT 6 FEET									

Figure 45, Log of Trench T43, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T44		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	ALLUVIUM Loose, dry, brown, Silty SAND				
2				SM/SC	Medium dense, slightly moist, dark yellowish brown, Clayey Silty SAND				
4					TRENCH TERMINATED AT 4 FEET				

Figure 46, Log of Trench T44, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL <input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... STANDARD PENETRATION TEST <input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED) <input type="checkbox"/> ... WATER TABLE OR SEEPAGE
---	---	--

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T45	ELEV. (MSL.)	DATE COMPLETED	10/19/2005	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)					
0				SM	ALLUVIUM		Loose to medium dense, reddish brown, Silty SAND									
2					TRENCH TERMINATED AT 5.5 FEET											
4																

Figure 47, Log of Trench T45, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T46		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	ALLUVIUM Loose, dry, dark yellowish brown, Silty SAND				
2				SM	Medium dense, moist, grayish brown, Silty SAND with caliche				
4					TRENCH TERMINATED AT 5 FEET				

Figure 48, Log of Trench T46, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/02/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T47		
					ELEV. (MSL.)	DATE COMPLETED	11/26/05
EQUIPMENT							CASE 580
0				SM	MATERIAL DESCRIPTION		
2					COVER FILL Medium dense, dark yellowish brown, Silty SAND		
4					LANDFILL DEBRIS		
6					TRENCH TERMINATED AT 6 FEET		

Figure 49, Log of Trench T47, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T48		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0				SM	ALLUVIUM Medium dense, dry, dark yellowish brown, Silty SAND				
2									
4					TRENCH TERMINATED AT 5 FEET				

Log of Trench T48, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T49			PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
					ELEV. (MSL.)	DATE COMPLETED	EQUIPMENT						
0				SM	MATERIAL DESCRIPTION								
2					ALLUVIUM Loose to medium dense, moist, dark brown, Silty SAND								
4													
6													
					TRENCH TERMINATED AT 7 FEET								

Log of Trench T49, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T50		
					ELEV. (MSL.)	DATE COMPLETED	11/26/2005
					EQUIPMENT	CASE 580	
0					MATERIAL DESCRIPTION		
0					LANDFILL DEBRIS - asphalt, concrete, rubble		
2				SM	ALLUVIUM Medium dense, dark yellowish brown, Silty SAND		
4							
6					TRENCH TERMINATED AT 6 FEET		

Log of Trench T50, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T51		
					ELEV. (MSL.)	DATE COMPLETED	11/26/2005
EQUIPMENT CASE 580							
0					MATERIAL DESCRIPTION		
0					LANDFILL DEBRIS - abundant asphalt concrete		
2				SM	ALLUVIUM Medium dense, moist, dark brown, Silty SAND		
4							
6							
					TRENCH TERMINATED AT 7 FEET		

Log of Trench T51, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T52		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
					ELEV. (MSL.)	DATE COMPLETED						
0				SM	MATERIAL DESCRIPTION							
0				SM	ALLUVIUM Medium dense, dark brown, Silty SAND							
2					TRENCH TERMINATED AT 3 FEET							

Log of Trench T52, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T53		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0					MATERIAL DESCRIPTION				
0		COVER FILL							
2		LANDFILL DEBRIS Loose, damp, dark brown, Silty SAND, with glass fragments, metal and ash							
4									
6									
8									
10									
12									
14									
16									
18									
20									
22		SP			ALLUVIUM Very dense, brown, SAND and gravel TRENCH TERMINATED AT 23 FEET				

Log of Trench T53, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T54		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)	
					ELEV. (MSL.)	DATE COMPLETED				
0					MATERIAL DESCRIPTION					
		COVER FILL								
2					LANDFILL DEBRIS					
		Loose, damp, dark brown, Silty SAND, with gravel, with glass fragments, metal, and ash								
4										
6										
8										
10										
		SP			ALLUVIUM					
					Dense to very dense, brown, Gravelly SAND					
					TRENCH TERMINATED AT 11 FEET					

Log of Trench T54, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T55		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	UNCONTROLLED FILL Medium dense to dense, Silty SAND with gravel - gravel clasts				
2									
4									
6									
8									
10									
12									
14					TRENCH TERMINATED AT 14.5 FEET				

Log of Trench T55, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T56		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	UNCONTROLLED FILL Medium dense to dense, brown, Silty SAND with gravel and cobbles				
2									
4									
6									
8									
10									
12									
14									
16									
18									
					TRENCH TERMINATED AT 19 FEET				

Log of Trench T56, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T57		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	UNCONTROLLED FILL Medium dense to dense, Silty SAND, with gravel, and cobbles <12				
2									
4									
6									
8									
10									
12									
14									
16									
18									
					TRENCH TERMINATED AT 18.5 FEET				

Log of Trench T57, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	SOIL CLASS (USCS)	GROUNDWATER	TRENCH T58		PENETRATION RESISTANCE (BLOWSIFT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0			GM		UNCONTROLLED FILL				
					Loose to medium dense, Silty Sandy GRAVEL				
					Medium, dense to moist, dark yellowish brown, Silty SAND with gravel, dips Southwest 10-20 degrees				
2									
4									
6									
8									
10									
12			SM		ALLUVIUM				
					Medium dense, moist, dark yellowish brown, Silty SAND with gravel				
14					TRENCH TERMINATED AT 14 FEET				

Log of Trench T58, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SET FORTH HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T59		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	UNCONTROLLED FILL Loose, Silty to Clayey SAND, with gravel, and gravel seams - dense to medium dense				
2									
4									
6				SM	ALLUVIUM Medium dense to dense, moist, dark yellowish brown, Silty SAND, with gravel				
8					TRENCH TERMINATED AT 8 FEET				

Log of Trench T59, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	SOIL CLASS (USCS)	GROUNDWATER	TRENCH T60		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0			GM		UNCONTROLLED FILL	Loose, dry, dark yellowish brown, Silty Sandy GRAVEL			
2									
4									
6			GM		ALLUVIUM	Medium dense to dense, pale yellowish brown, Silty Sandy GRAVEL			
8					TRENCH TERMINATED AT 8.5 FEET				

Log of Trench T60, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T61		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0		0-0-0 0-0-0 6-0-0 0-0-0 0-0-0		GP	UNCONTROLLED FILL Medium dense, pale yellowish brown, Silty Sandy GRAVEL				
2				CL	ALLUVIUM Hard, slightly moist, yellowish brown, Sandy CLAY				
4					TRENCH TERMINATED AT 5 FEET				

Log of Trench T61, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T62		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SP	UNCONTROLLED FILL Medium dense to dense, Silty SAND/Gravelly SAND with occasional debris and asphalt				
2									
4									
6									
8									
10									
12									
14									
16					TRENCH TERMINATED AT 16 FEET				

Log of Trench T62, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T63		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)					
					ELEV. (MSL.)	DATE COMPLETED								
					EQUIPMENT	TRACKHOE								
MATERIAL DESCRIPTION														
0				ML	ALLUVIUM Hard, moist, grayish brown, Clayey SILT									
2				GP	Medium dense, moist, gray, Sandy GRAVEL with ferrous oxide stains									
4					TRENCH TERMINATED AT 5 FEET									

Log of Trench T63, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T64		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.) _____ DATE COMPLETED <u>11/22/2005</u>				
					EQUIPMENT <u>TRACKHOE</u>				
					MATERIAL DESCRIPTION				
0				ML	ALLUVIUM Soft, dry, gray, Sandy SILT				
2				ML	Firm, moist, yellowish brown to reddish brown, Clayey Sandy SILT				
4					TRENCH TERMINATED AT 4.5 FEET				



Log of Trench T64, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN THEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T65			PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
				ELEV. (MSL.) _____ DATE COMPLETED <u>11/22/2005</u>			EQUIPMENT <u>TRACKHOE</u>						
MATERIAL DESCRIPTION													
0				GM	UNCONTROLLED FILL Loose, dry, dark yellowish brown, Silty Sandy GRAVEL								
2				GM	ALLUVIUM Medium dense, moist, ferrous oxide stained, Silty Sandy GRAVEL, with sand lenses								
4					TRENCH TERMINATED AT 5 FEET								

Log of Trench T65, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T66			PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED	11/22/2005			
MATERIAL DESCRIPTION										
0				GP	UNCONTROLLED FILL Medium dense, yellowish brown to ferrous oxide stained, Sandy GRAVEL					
2										
4										
6										
8		SM			ALLUVIUM Medium dense to loose, dark brown, Silty SAND with gravel		TRENCH TERMINATED AT 8 FEET			

Log of Trench T66, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T67		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
					ELEV. (MSL.)	DATE COMPLETED						
0					MATERIAL DESCRIPTION							
					UNCONTROLLED FILL							
2		GM		SM	ALLUVIUM Silty Sandy GRAVEL Medium dense to dense, moist, orange brown ferrous oxide, Silty SAND with gravel							
6					TRENCH TERMINATED AT 6 FEET							

Log of Trench T67, page 1 of 1

TRENCH LOG DESTINATION TRENCHES GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input checked="" type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T68			PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED	11/29/2005			
MATERIAL DESCRIPTION										
0				SM	UNCONTROLLED FILL Medium dense to dense, Silty SAND and Sandy GRAVEL					
2										
4										
6				SM/ML	ALLUVIUM Dense, moist, orange brown mottled, Silty SAND and Sandy SILT					
8					TRENCH TERMINATED AT 8.5 FEET					

Log of Trench T68, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T69		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM	UNCONTROLLED FILL Medium dense, moist, Silty SAND, with trace gravel				
2									
4									
6									
8									
10									
12				SM	ALLUVIUM Dense, moist, grayish green, Silty SAND, with caliche veins				
					TRENCH TERMINATED AT 12 FEET				

Log of Trench T69, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL <input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... STANDARD PENETRATION TEST <input type="checkbox"/> ... CHUNK SAMPLE	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED) <input type="checkbox"/> ... WATER TABLE OR SEEPAGE
---	---	---

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T70		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)			
					ELEV. (MSL.)	DATE COMPLETED						
					MATERIAL DESCRIPTION							
0				SM	UNCONTROLLED FILL Medium dense, moist, Silty SAND/Sandy GRAVEL							
2												
4												
6												
8												
10												
12				SM	ALLUVIUM Dense, moist, dark brown, Silty SAND, dips north 10 degrees							
					TRENCH TERMINATED AT 13.5 FEET							

Log of Trench T70, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS

... SAMPLING UNSUCCESSFUL ... STANDARD PENETRATION TEST ... DRIVE SAMPLE (UNDISTURBED)
 ... DISTURBED OR BAG SAMPLE ... CHUNK SAMPLE ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SET FORTH HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T71		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
0				SM	MATERIAL DESCRIPTION				
0				SM	UNCONTROLLED FILL Medium dense, dry to moist, Silty SAND, with gravel				
2									
4									
6									
8									
10									
12									
14									
16				GC	Medium dense, moist, dark brown, Clayey GRAVEL				
					TRENCH TERMINATED AT 17 FEET				

Log of Trench T71, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS

<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T72	PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
0				SM/ML	ELEV. (MSL.) _____ DATE COMPLETED <u>11/22/2005</u> EQUIPMENT <u>TRACKHOE</u>			
2					MATERIAL DESCRIPTION ALLUVIUM Medium dense, slightly moist, dark yellowish brown, Silty SAND/Sandy SILT			
					TRENCH TERMINATED AT 2 FEET			
MATERIAL DESCRIPTION								

Log of Trench T72, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input checked="" type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.

PROJECT NO. R8259-06-03

DEPTH IN FEET	SAMPLE NO.	LITHOLOGY	GROUNDWATER	SOIL CLASS (USCS)	TRENCH T73		PENETRATION RESISTANCE (BLOWS/FT.)	DRY DENSITY (P.C.F.)	MOISTURE CONTENT (%)
					ELEV. (MSL.)	DATE COMPLETED			
MATERIAL DESCRIPTION									
0				SM-SP	UNCONTROLLED FILL Medium dense, moist, dark yellowish brown to gray (glazed), Silty SAND/Gravelly SAND				
2									
4									
6									
8									
10					TRENCH TERMINATED AT 10 FEET				

Log of Trench T73, page 1 of 1

TRENCH LOG DESTINATION TRENCHES.GPJ 02/13/06

SAMPLE SYMBOLS	<input type="checkbox"/> ... SAMPLING UNSUCCESSFUL	<input type="checkbox"/> ... STANDARD PENETRATION TEST	<input type="checkbox"/> ... DRIVE SAMPLE (UNDISTURBED)
	<input checked="" type="checkbox"/> ... DISTURBED OR BAG SAMPLE	<input type="checkbox"/> ... CHUNK SAMPLE	<input type="checkbox"/> ... WATER TABLE OR SEEPAGE

NOTE: THE LOG OF SUBSURFACE CONDITIONS SHOWN HEREON APPLIES ONLY AT THE SPECIFIC BORING OR TRENCH LOCATION AND AT THE DATE INDICATED. IT IS NOT WARRANTED TO BE
REPRESENTATIVE OF SUBSURFACE CONDITIONS AT OTHER LOCATIONS AND TIMES.


APPENDIX


B

APPENDIX B

LABORATORY TESTING PROGRAM

Laboratory tests were performed in accordance with generally accepted test methods of the American Society for Testing and Materials (ASTM) or other suggested procedures. Selected soil samples were tested for their in-place dry density and moisture content, grain-size distribution, and plasticity characteristics. The results of the laboratory tests are presented on the following pages. In-place dry density, fines (-200) content and moisture content of selected samples are also presented on the exploratory logs in Appendix A.





COBBLES	GRAVEL		SAND			SILT OR CLAY
	coarse	fine	coarse	medium	fine	

Specimen Identification	Classification					LL	PL	PI	Cc	Cu
-------------------------	----------------	--	--	--	--	----	----	----	----	----

●	BH-6	5.9	Sandy Silt/Silty Sand							
☒	BH-7	5.7	Clayey Silty Sand							

Specimen Identification	D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay
-------------------------	------	-----	-----	-----	---------	-------	-------	-------

●	BH-6	5.9	0.075					41.9
☒	BH-7	5.7	75	0.457		0.0	48.3	38.7



Geocon Consultants, Inc.
1167 Annie Court, Suite B
Minden, Nevada 89423
Telephone: 775.267.0566
Fax: 775.267.0728

GRAIN SIZE DISTRIBUTION

Project: Destination Nevada
Location: Carson City
Number: R8259-06-01


APPENDIX

C

APPENDIX C

SOIL CONSERVATION SERVICE DATA

The information contained herein is taken from the Soil Survey of the Carson City Area, Nevada, 1979. The information is limited to the top five feet of soil and was compiled prior before the mass grading that was performed on the site during the 1980's. This data is relevant to the undisturbed portions of the site and indicates to a lesser extent the type of materials that are found in the uncontrolled fills.



SCS Map

Destination Nevada

Carson City,
Nevada

GEOCON

CONSULTANTS, INC.
1167 ANNIE COURT • SUITE B • MINDEN, NV 89423
PHONE 775 267-0566 • FAX 775 267-0728



R8259-06-02

Feb-06

FIGURE-C1

SOIL SURVEY

TABLE 13.--ENGINEERING PROPERTIES AND CLASSIFICATIONS--Continued

Soil name and map symbol	Depth	USDA texture	Classification		Frag- ments > 3 inches	Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO		2	10	40	200		
Reno: 54-----	10				Pet					Pet	
	0-3	Cobbly fine sandy loam.	SM	A-1, A-2	15-30	65-85	60-80	50-65	20-35	15-25	NP-5
	3-24	Clay, sandy clay	SC, CH, CL	A-7	0-5	80-100	75-95	60-85	45-75	45-55	25-35
	24-29	Cemented-----	-----	-----	-----	-----	-----	-----	-----	-----	-----
	29-60	Very gravelly loamy sand.	GP-GM, GM	A-1	5-10	30-55	20-50	15-30	5-15	-----	NP
	55-----	0-3	Gravelly clay loam.	GC, CL	A-6	0	65-75	60-75	55-70	45-55	35-40
	3-20	Clay, sandy clay	SC, CH, CL	A-7	0-5	80-100	75-95	60-85	45-75	45-55	25-35
	20-29	Cemented-----	-----	-----	-----	-----	-----	-----	-----	-----	-----
	29-60	Very gravelly loamy sand.	GP-GM, GM	A-1	5-10	30-55	20-50	15-30	5-15	-----	NP

CARSON CITY AREA, NEVADA

TABLE 14.--PHYSICAL AND CHEMICAL PROPERTIES OF SOILS--Continued

Soil name and map symbol	Depth	Permeability	Available water capacity	Soil reaction	Salinity	Shrink-swell potential	Risk of corrosion		Erosion factors	Wind erodibility	group
							Uncoated steel	Concrete			
Reno: 54-----	10	In/hr	In/in	pH	Mhos/cm						
	0-3	2.0-6.0	0.08-0.12	6.1-7.3	<2	Low	Moderate	Low	0.17	2	4
	3-24	<0.06	0.14-0.16	6.1-7.8	<2	High	High	Low	0.24		
	24-29	---	---	---	---	---	---	---			
	29-60	>6.0	0.05-0.07	7.4-8.4	<4	Low	High	Low	0.15		
	55-----	0-3	0.2-0.6	0.16-0.18	6.1-7.3	<2	Moderate	Moderate	Low	0.32	2
	3-20	<0.06	0.14-0.16	6.1-7.8	<2	High	High	Low	0.24		7
	20-29	---	---	---	---	---	---	---			
	29-60	>6.0	0.05-0.07	7.4-8.4	<4	Low	High	Low	0.15		

SCS SOIL DATA

GEOCON

CONSULTANTS, INC.

1167 ANNIE COURT - SUITE B - MINDEN, NV 89423
PHONE 775 267-0566 - FAX 775 267-0728

Destination Nevada

Carson City,
Nevada

R8259-06-02

Feb-06

FIGURE-C2