



## TYPICAL PAVEMENT SECTION

1. PARKING LOTS WILL BE CONSTRUCTED WITH A MINIMUM OF 2.5 INCHES OF A.C. SURFACE ON 6 INCHES OF TYPE 2 CLASS B AGGREGATE BASE (BOTH COMPAKTED TO 95% MIN.)

## WHEEL STOPS

1. WHEEL STOPS WILL BE 2 FEET (MIN.) FROM PROPERTY LINE OR APPURTENANCES.
2. WHEEL STOP WILL BE SECURED WITH 0.5 INCH REBAR DRIVEN 12 INCHES (MIN.) INTO SURFACE OR WITH AN APPROVED EPOXY HAVING A SETTING TIME OF 4-HOUR (MAX.) AT 77 DEGREES FAHRENHEIT.
3. WHEEL STOPS WILL BE WHITE OR SAFETY YELLOW WITH 0.25 CANDLE POWER REFLECTIVITY.
4. WHEEL STOP DIMENSIONS WILL BE 4 INCHES TO 7 INCHES HIGH X 4 FEET (MIN.) LONG X 6 INCHES (MIN.) WIDE. WHEEL STOP LOCATION SHALL SECURE VEHICLE TIRES.
5. MINIMUM WALL THICKNESS FOR METAL STOPS WILL BE 0.25 INCHES, FOR POLYETHYLENE OR FIBERGLASS WHEEL STOPS - 0.75 INCHES.
6. WOOD WHEEL STOPS WILL BE REDWOOD #2 OR BETTER.
7. CONCRETE WHEEL STOPS WILL HAVE A MINIMUM TENSILE STRENGTH OF 2000 P.S.I. (ASTM D-746).
8. IMPACT BRITTLE TEMPERATURE SHALL BE -75 DEGREES CELSIUS. (ASTM D-746).
9. ELONGATION SHALL BE LIMITED TO 35 PERCENT AT 73 DEGREES FAHRENHEIT (ASTM D638).

## STRIPING

1. PARKING LOT STRIPING SHALL BE WHITE WITH A MINIMUM WIDTH OF 4 INCHES. PAINT SHALL BE SPECIFIED "TRAFFIC STRIPING PAINT" OR HAVE MANUFACTURER'S CERTIFICATION OF SUITABLE APPLICATION ON ASPHALTIC OR CONCRETE SURFACES.

## LIGHTING

1. APPLICATION LEVEL WILL BE 1.0 FOOT CANDLES (MIN.) WITH A UNIFORMITY RATIO (AVERAGE ILLUMINATION) NOT EXCEEDING 6:1 AND AS APPROVED BY THE PUBLIC WORKS DEPARTMENT DEPENDING ON PEDESTRIAN VOLUMES.
2. LIGHT FIXTURES SHALL BE FULL CUT-OFF FIXTURES AS DEFINED BY THE ILLUMINATING ENGINEERING SOCIETY OF NORTH AMERICA (IESNA) UNLESS OTHERWISE APPROVED BY THE CARSON CITY ENGINEER OR PUBLIC WORKS DIRECTOR.
3. LIGHT POLES SHALL BE LOCATED TO ELIMINATE INTERFERENCE WITH VEHICULAR OR PEDESTRIAN TRAFFIC (AT THE END OF PARKING ROWS WHEN PRACTICAL) AND AS APPROVED BY THE PUBLIC WORKS DEPARTMENT. POLES SHALL NOT BE LOCATED NEXT TO TREES.
4. MOUNTING POLES WILL COMPLY WITH THE SAME SPECIFICATIONS PRESCRIBED FOR URBAN COLLECTOR STREET USE.

NO.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	SECTION
1	RENUMBER	3/22	<b>PARKING LOT REQUIREMENTS</b>	CARSON CITY
				DRAWING NO. C-5.5.1.3
				DATE MAR 2022
APPROVED BY: <u>  </u>	3/22			